

# MIC® Tight Buffer Indoor Cable 24F G50 MMF ClearCurve® OM4 0.9mm TB3, Cca-s1a,d1,a1



CORNING

**Part Number:**  
**024T8Z-32198E2G**

Corning LANscape® indoor cables can be deployed indoor as building backbone (riser) cabling as well as for the cabling between floor distributors.

The tight-buffered construction facilitates easier termination for low-fiber-count applications in the local area network (LAN) and eliminates need for fan-out kits.

## Features and Benefits

### **All-dielectric cable construction**

Requires no grounding or bonding

---

### **Small diameter and bend radius**

Easy installation in space-constrained areas

---

### **TB3 tight-buffered construction**

Easy and consistent stripping over 10 cm

---

### **Silicon-free outer jacket**

The cable jacket and the outer jacket of subunits (not valid for 900 µm tight buffers) are free of harmful components to paint structures

---

### **Flame retardant**

LSZH™/FRNC

# MIC® Tight Buffer Indoor Cable 24F G50 MMF ClearCurve® OM4 0.9mm TB3, Cca-s1a,d1,a1

CORNING

## Specifications

### Mechanical Specifications

Crush resistance	1000 N/10 cm
Fire load	1.13 MJ/m
Max. tensile strength for installation	1000 N
Min. bend radius installation	120 mm
Min. bend radius operation	80 mm
Nominal outer diameter	8 mm

### Cable Design

Cable marking	Metre - Handset - CE 17 EN 50575 Cca-s1a,d1,a1 - Sine - CORNING - Fiber Optic Cable - Year - MIC(R) J-V(ZN)H 24 OM4CC TB3 0.9 LSZH(TM)/FRNC
Central element	Yarn
Fibre count	24
Number of ripcords	1
Outer jacket colour	Turquoise
Buffering diameter	900 µm
Outer jacket material	Flame-retardant, non-corrosive/low-smoke, silicon-free, zero-halogen (FRNC/LSZH) material
Tensile strength elements and/or armouring - Layer 1	Aramid yarn
Tight buffer type	TB3 (easy strip up to 10 cm)
Flame rating	LSZH™/FRNC

### Environmental Conditions

Temperature range, installation	-5 °C to 50 °C
Temperature range, storage	-25 °C to 70 °C
Temperature range, operation	-20 °C to 60 °C

# MIC® Tight Buffer Indoor Cable 24F G50 MMF ClearCurve® OM4 0.9mm TB3, Cca-s1a,d1,a1

CORNING

## General Specifications

Environment	Indoor
Cable type	Tight-buffered
Product type	Dielectric
Fibre category	50 µm MM (OM4)
Flame rating	LSZH™/FRNC
Coding according to EN 60794-1-1 (DIN VDE 0888-100-1)	J-V(ZN)H
Application	Vertical Riser, General Purpose Horizontal, Indoor horizontal, General building applications

## Ordering Information

Product Number	024T8Z-32198E2G
EAN Code	4056418099514
Maximum delivery length	4000 m
Weight	59 kg/km

## Standards

Reaction to fire	Cca, s1a, d1, a1
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable) and IEC 60332-3-24 (bunch of cables)
Reaction to fire requirements	Reaction to fire according to EN 50575 and EN 13501-6
Smoke density	Low Smoke to IEC 61034
Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

## Optical Characteristics

Fibre code	T
Fibre name	G50/125 ULTRA-BEND 7.5

# MIC® Tight Buffer Indoor Cable 24F G50 MMF ClearCurve® OM4 0.9mm TB3, Cca-s1a,d1,a1

CORNING

Optical Characteristics	
Fibre Type	Multimode
Fibre core diameter	50 µm
Minimum effective modal bandwidth (EMB)	4700 MHz*km / -
Maximum Attenuation	2.8 dB/km / 1.0 dB/km
Min. overfilled launch (OFL) bandwidth	3500 MHz*km / 500 MHz*km
Serial 1 gigabit ethernet	1100 MHz*km / 600 MHz*km
Serial 10 gigabit ethernet	550 MHz*km / -
Typical attenuation	2.4 dB/km / 0.8 dB/km
Wavelengths	850 nm / 1300 nm
Induced Attenuation	For 7.5 mm radius < 0.2 db / -
Fibre category	OM4



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.