

# Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, Dca 4P, Green, 500m



**Part Number:**  
**MCXEDE-DD047-V004-L6**

The Everon™ Copper Datacom F/UTP 550/24 cable is designed up to 550MHz and its transmission characteristics exceed Category 6A specifications according to EN50288-10-1 IEC 61156-5.

High system margins for the complete link according to the last version of ISO/IEC 11801 and EN 50173 (Series) will be achieved by using corresponding hardware together with this highend copper cable.

The cable has a streamlined construction and low weight.

Overall shielding with with a Allaminated foil and each twisted pair unshielded (F/UTP). The cable satisfies Class B interference radiation standards according to EN 55022, as well as immunity according to EN 55024, which enables the realization of CE-compatible networks.

## Features and Benefits

F/UTP 550/24 cable designed up to 550 MHz

---

Fulfils all requirements of category EN50288-10-1 and IEC 61156-5

---

Suitable for Classe D to EA according to ISO/IEC 11801. EN50173 and 10 Gigabit Ethernet according to IEEE 802.3an

---

Tested and approved for Power over Ethernet applications (PoE/PoE+/4PPoE) according to IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt up to 90W

---

Low smoke and halogen-free (LSZH)

---

Overall shielding with with a Allaminated foil and each twisted pair unshielded (F/UTP)

---

Length marking on jacket

---

Dca-s2,d2,a1

# Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, Dca 4P, Green, 500m

CORNING

## Specifications

### General Specifications

Construction	Simplex, 4P
Legacy Part Number	VOL6AFL4500
Environment	Indoor
Category	6A
Cable type	F/UTP
Bandwidth	550 MHz
Halogen-free	Yes
Reaction to fire	Dca, s2, d2, a1

### Mechanical Characteristics

Fire load	710 MJ/m
Nominal outer diameter	7 mm
Min. bend radius installation	8x Cable-Ø
Maximum tensile strength	90 N

### Ordering Information

Product Number	MCXEDE-DD047-V004-L6
Length	500 m
Weight	48 kg
Packing type	Drum

### Environmental Conditions

Temperature range, installation	0 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C

# Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, Dca 4P, Green, 500m



Cable Design	
Conductor	AWG 24
Conductor insulation	Halogen-free foam-skin material
Twisting	2 cores to a pair
Outer jacket material	LSZH™
Outer jacket colour	Green

Electrical Characteristics	
Conductor resistance unbalance	2 %
Delay skew	40 ns/100 m
Max. loop resistance	190 Ω/km
Propagation delay	520 ns/m
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max
Surface transfer impedance	10 mΩ
Propagation velocity at >10 MHz (NVP*c)	78 %
Coupling attenuation	55 dB
Insulation Resistance	> 5000 MΩ.km

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 61156-5; EN 50288-6-1, ISO/IEC 11801 Ed. 2.2; EN 50173-1, ANSI/TIA-568-C-2; IEC 60304, EN 50288-10-1, ISO/IEC 11801 Ed. 2.2; EN 50173-1, ANSI/TIA -568-C-2; IEC60304
Design And Test Criteria	Compliant with PoE / PoE++ IEEE 802.3af, IEEE 802.3atIEEE 802.3 an 1000 Base-T
Flame propagation test	Flame retardant according to IEC 60332-1 and EN 50265-2-1
Smoke density	IEC 61034-2
Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

# Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, Dca 4P, Green, 500m

CORNING

Electrical Characteristics								
Frequency [MHz]	4	10	20	63	100	250	500	550
Attenuation according to Standard [db/100m]	3.8	5.93	8.38	14.99	19.14	31.1	45.26	47.7
Typical attenuation [db/100m]	3.6	5.5	7.9	14.5	18.5	30.0	43.0	50.0
NEXT according to Standard [db/100m]	66.27	60.3	55.78	48.36	45.3	39.3	34.82	34.19
Typical NEXT Values [db/100m]	71.0	65.0	61.0	53.0	50.0	44.0	40.0	39.0
ACR-N according to Standard [db/100m]	55.96	48.0	41.98	32.08	28.0	8.3	14.02	13.19
Typical ACR-N Values [db/100m]	78.0	70.0	64.0	54.0	50.0	45.0	40.0	39.0



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany  
 +00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.