

# FutureCom™ U/UTP 550/24, Category 6A, LSZH™/FRNC, Cca 4P, Green



CORNING

**Part Number:**  
**UU009161595**

FutureCom™ U/UTP 550/24, LSZH Cable: twisted pair,  
covered by a LSOH jacket, spec. up to 550 MHz, AWG 24,  
Cat.6A acc. ISO/IEC11801 Cca-s1a,d0,a1

## Features and Benefits

U/UTP 550/24 copper cable specified up to 550 MHz

---

Fulfills all requirements of Cat.6 acc. according to EN  
50288-11-1 and IEC 61156-5

---

Ensures high system margins according ISO/IEC 11801  
Ed.2.2 (2011) and EN 50173-1 series (2011)

---

Twisted pair, covered by a LSZH Jacket, CPR Cca-  
s1a,d0,a1

---

Satisfies Class B + interference radiation as well as  
immunity standards (EN 55022 and EN 55024)

---

Supports Power over Ethernet (PoE / PoE+) according  
IEEE 802.3at

# FutureCom™ U/UTP 550/24, Category 6A, LSZH™/FRNC, Cca 4P, Green

CORNING

## Specifications

### Environmental Conditions

Temperature Range, Installation	0 °C to 50 °C
Temperature Range, Operation	-20 °C to 60 °C

### General Specifications

Environment	Indoor
Category	6A
Cable Type	U/UTP
Bandwidth	500 MHz
Halogen-free	Yes
Construction	Simplex, 4P
Reaction to fire	Cca, s1a, d0, a1
Legacy Part Number	VOL6AUL4500

### Cable Design

Conductor	Copper Wire, AWG 24
Conductor Insulation	Solid PE
Twisting	2 cores to a pair
Outer Jacket Material	LSZH™
Outer Jacket Color	Green

### Mechanical Specifications

Fire Load	630 MJ/m
Nominal Outer Diameter	7.6 mm
Min. Bend Radius Installation	8x Cable-Ø (over flat side)
Maximum Tensile Strength	80 N

# FutureCom™ U/UTP 550/24, Category 6A, LSZH™/FRNC, Cca 4P, Green



Electrical Characteristics	
Conductor resistance unbalance	2 %
Delay skew	45 ns/100 m
Max. loop resistance	190 MΩ*km
Propagation delay	545 ns/100 m
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max
Insulation Resistance	5000 MΩ*km
Propagation Velocity at >10 MHz (NVP*c)	69 %
Coupling Attenuation	40 dB

Ordering Information	
Product Number	UU009161595
Length	500 m
Weight	49 kg
Packing Type	Drum

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 61156-5; EN 50288-11-1, ISO/IEC 11801 Ed. 2.2; EN 50173-1, ANSI/TIA -568-C-2; IEC60304
Design and Test Criteria	Compliant with PoE / PoE++ IEEE 802.3af, IEEE 802.3atIEEE 802.3 an 1000 Base-T
Smoke density	Low Smoke to IEC 61034
Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Electrical Characteristics								
Frequency [MHz]	4	10	20	63	100	250	500	550

# FutureCom™ U/UTP 550/24, Category 6A, LSZH™/FRNC, Cca 4P, Green

CORNING

## Electrical Characteristics

Attenuation according to Standard [db/100m]	3.8	5.9	8.4	15.0	19.1	31.1	45.3	
Typical attenuation [db/100m]	3.6	5.5	7.9	14.5	18.5	30.0	43.0	50.0
NEXT according to Standard [db/100m]	66.3	60.3	55.8	48.4	45.3	39.3	34.8	
Typical NEXT Values [db/100m]	71.0	65.0	61.0	53.0	50.0	44.0	40.0	39.0
ACR-N according to Standard [db/100m]	62.5	54.4	47.4	33.4	26.2	8.3	-10.4	
Typical ACR-N Values [db/100m]	78.0	70.0	64.0	54.0	50.0	45.0	40.0	39.0



Corning Optical Communications GmbH & Co. KG • Lelziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.