

FutureCom™ V250 Shielded VOLOCK6SH8, V250S Jack, RJ45 Vol, Cat6, Bag/8, White

CORNING

Part Number:
XF500006010

Our Cat.6 copper interconnect products work together to provide an easy-to-use solution for deploying high-speed connections throughout a building. The RJ45 jack is a key component in this system. These RJ45 jacks have been certified by an independent test laboratory to hardware certification. Each jack component is able to terminate to any certified Cat.6 TIA, ISO/IEC and EN standards for hardware performance, confirmed by independent laboratory certifications. The jack's unique three cable entry points help make installation simple. The traditional one-click design enables an easy, tool-less termination on Cat. 6 shielded twisted pair cables, meeting industry performance standards.

Features and Benefits

Tool-less jack

Easy and quick to install - reliable connection
The conductors are wired in a single operation

Three cable entry points

Less cable bending required - better compliance with minimum bend radius

Reusable

Jack can be reused even after wiring mistake

No untwisting of pairs before termination

Minimized stripping length - limited pair untwist - pairs kept together, no wire guide required

Clip-in mounting

Designed to fit many other accessories

Accepts solid and stranded conductors

Enables "jack-to-plug" cables to be manufactured using stranded conductors

Integral shutter


No additional shuttering required on faceplates

Hardware Performance

Can be mixed and matched with other Hardware certified copper cable and patchcords

IEEE 802.3bt-2018 performance (4PoE)

Ready for new applications powered on 4 pairs up to 90W



FutureCom™ V250 Jack, VOLOCK6SH8, V250S, RJ45 Vol, Cat6, Bag/8, White

FutureCom™ V250 Shielded VOLOCK6SH8, V250S Jack, RJ45 Vol, Cat6, Bag/8, White



Specifications

Design	
Housing material	Metal
Colour	White
Conductor	AWG 24 - 22
Jack Type	RJ45 - 8/8
Insulation diameter max.	1.6 mm
Number of Stranded Wires	7

Mechanical Specifications	
Contact surface	Gold, 1.27 µm
Reproducibility	Several times reusable
Solid Wire Diameter	0.5 mm to 0.65 mm
Stranded Wire Diameter	0.15 mm to 0.2 mm

General Specifications	
Category	6

Dimensions	
Length	38 mm
Height	25 mm
Width	18 mm

Ordering Information	
Product Number	XF500006010
Packaging method	Bag of 8 / 1 Box
Packing Weight	1.35 kg

FutureCom™ V250 Shielded VOLOCK6SH8, V250S Jack, RJ45 Vol, Cat6, Bag/8, White



Ordering Information	
Units per delivery	96/1

Standards	
Approvals and Listings	ISO/ IEC 11801 Edition 2. Arm 1-2, EN 50173-1, ANSI/ TIA/ EIA-568-C.2-2009, IEC 60512-99-001, ISO/IEC 60603-7-5
Design And Test Criteria	IEEE 802.3 1GBASE-T, IEEE 802.3at

Environmental Conditions	
Temperature range, operation	-10 °C to 60 °C

Electrical Specifications	
Lead Through Resistance	< 200 MΩ
Insulation resistance	> 500 MΩ
Voltage Rating (Maximum)	<75 VDC



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.